


ÓŚRODEK BADAWCZO-ROZWOJOWY PRZEMYSŁU RAFINERYJNEGO
SPÓŁKA AKCYJNA

09-411 Płock, ul. Chemików 5, POLSKA

www.obr.pl



CE
1488
07

DECLARATION OF CONFORMITY No. 3472 c

1. Building product manufacturer and production plant:

Ośrodek Badawczo-Rozwojowy Przemysłu Rafineryjnego Spółka Akcyjna

09-411 Płock ul. Chemików 5

09-407 Płock ul. Otolińska 25

2. Name and description of the building product, including the type:

Geomembrane GEOCHRON made from PEHD , smooth or one side or both sides textured. Thickness 1,0 ; 1,5 ; 2,0 ; 2,5 mm and width of 5000mm.

3. Statistic qualification

Polish Classification of manufactured goods no 25.21.30-17.00

4. Applicaton and its range

- sealing of the municipal waste lanfill. The geomembrane with more than 2,0mm thickness can be used. For the surface sealing the thickness 1,5 mm and more is approved.
- sealing in the area of liquid gas storage and distribution with geomembrane with thickness 1,5 mm and more.
- sealing of the city sludge refinery station with geomembrane thickness 1,5 mm and more.
- sealing of engineering constructions also the hydrotechnic types.

Geomembranes have to be applied according to the technical documentation of given object, including building norms and technical properties of the goods manufactured.

5. Technical specification

Technical Approval ITB AT – 15 – 3472/2005 with date 30.09.2005 together with the appendix No 1 dated 05.06.2007 and with appendix No 2 dated 20.07.2007.

**6. Declared technical characteristics of building article type:
According to the technical specification / in appendix/**

**7. Notified unit participating in the conformity evaluation of the building product.
Instytut Techniki Budowlanej. Notified unit No. 1488.**

Certificate of the Factory Production Control No. ITB – 0008/Z dated 08.10.2007.

Item	Properties	Demands				Test methods
		1.0 mm	1.5 mm	2.0 mm	2.5 mm	
1	2	3	4	5	6	7
1	Semblance	Black colour film with equal and straight edges , smooth or single / double tectured surface without bubbles and mechanical damages.				ZUAT – 15/IV.01/2003
2	Thickness ²⁾ , mm	1,0± 10%	1,5± 10%	2,0± 10%	2,5± 10%	PN-ISO 4593:1999
3	Strip width, mm	5000 + 4%				PN-ISO PN-90/B-04615
4	Surface weight, g/m ²	950 ± 10%	1420± 10%	1895± 10%	2370± 10%	PN-EN 1849-2:2004
5	Density, g/cm ³	≥ 0,94				PN-92/C-89035
6	Tensile stress at plasticity range, MPa: — along, — across	≥15 ≥15				PN-81/C-89034 PN-EN ISO 527-2:1998 sample type 1BA v = 100 ± 10 mm/min
7	Relative elongation at plasticity range, %: — along — across	≥10 ≥10				
8	Maximal tightness at extension, MPa: — along, — across	≥25 ≥25				
9	Relative elongation at break, %: — along, — across	≥600 ≥600				
10	Water permeability (72 h; 0,4 MPa)	watertight				
11	Flexibility while bowing on 5 mm dia cylinder at temp. -20°C.	No splits or cracks.				ZUAT – 15/IV.01/2003
12	Linear dimensions stabilization for small sized samples (80°C, 6h), % - along - across	≤0,5 ≤0,5				
13	Waterabsorbent, %	≤0,5				
14	Atmospherical obsolescence – accelerated by xenon method (110 MJ/m ²) - semblance	No splits , cracks, bubbles ; can appear slight colour change.				ZUAT –15/IV.01/2003
	- Maximal tensile elongation stress change (along), %	≤15				
	- Relative elongation at break change (along), %	≤15				
15	. Test baths pH 9,0 and pH 4,5 influence - semblance	-	No splits , cracks, bubbles ; can appear slight colour change.			

	- absorptivity, %	-	$\leq 5,0$			
	- linear parameters value change :					
	- along	-	$\leq 2,0$			
	- across	-	$\leq 2,0$			
	- Maximal tensile elongation stress change (along), %	-	≤ 15			
	- Relative elongation at break change (along), %	-	≤ 15			
16	Etyline and diesel oil effect					PN-EN ISO 175:2002 ²⁾
	- semblance	-	No splits , cracks, bubbles ; can appear slight colour change.			
	- weight change, %	-	$\leq 10,0$			
	- linear parameters value change :					
	- along	-	$\leq 5,0$			
	- across	-	$\leq 5,0$			
	- Maximal tensile elongation stress change (along), %	-	≤ 15			
	- Relative elongation at break change (along), %	-	≤ 15			
17	Maximal strength while puncture, N	≥ 3000	≥ 4800	≥ 5000	≥ 7000	PN-EN ISO 12236:1998
18	Chemical resistance					PN-EN ISO 175:2002
		1) for permanent aggressive environment influence defined by: a/ weight change after 8 weeks of aggressive environment influence % - 5% hydrochloric acid solution - 1% sodium hydroxide solution - 0,1% sodium chlorate solution - 2% detergent solution - 0,5% phenol solution - manure b/ Semblance change after 8 weeks of aggressive environment influence.	-	Weight gain ≤ 3 Weight loss ≤ 1		
	2) for periodic aggressive environment influence defined by: a/ weight change after 8 weeks of aggressive environment influence and after drying the samples to constant weight %. - 5% hydrochloric acid solution - 1% sodium hydroxide - 0,1% sodium chlorate solution - 2% detergent solution - 0,5% phenol solution - manure b/ Semblance change after 8 weeks of aggressive environment influence and after drying the samples to constant weight %	-	Weight gain ≤ 5 Weight loss ≤ 3		No changes or becoming mat with slight colour change.	

1/ In case of texturex geomembranes – concerns the outcome thickness (without carried PE fibres)

2/ during the tests the supposed medium infecting on samples are : Etyline E95 (time of application – 3 days) and diesel oil according to PN-EN 590:2002 (time of application – 28 days).

Geomembrane is also available in thickenss 0,70 and 0,75 mm.

Documents:

Technical Approval ITB nr AT-15-3472/2005

Technical Approval IBDiM nr AT/2004-04-0675

Plant Production Control Certyficat No ITB-0008/Z

Hygenic Atest PZH HK/B/0098/01/2005

Declaration of conformity 675a

Declaration of conformity 3472c